

PHYSICS (SPECIFICATION A)

PA01

Unit 1 Particles, Radiation and Quantum Phenomena

Data Sheet

Fundamental constants and values				Mechanics and Applied Physics		Fields, Waves, Quantum Phenomena	
Quantity	Symbol	Value	Units				
speed of light in vacuo	c	3.00×10^8	m s^{-1}	$v = u + at$		$g = \frac{F}{m}$	
permeability of free space	μ_0	$4\pi \times 10^{-7}$	H m^{-1}	$s = \left(\frac{u+v}{2}\right)t$		$g = -\frac{GM}{r^2}$	
permittivity of free space	ϵ_0	8.85×10^{-12}	F m^{-1}	$s = ut + \frac{at^2}{2}$		$g = -\frac{\Delta V}{\Delta x}$	
charge of electron	e	1.60×10^{-19}	C	$v^2 = u^2 + 2as$		$V = -\frac{GM}{r}$	
the Planck constant	h	6.63×10^{-34}	J s	$F = \frac{\Delta(mv)}{\Delta t}$		$a = -(2\pi f)^2 x$	
gravitational constant	G	6.67×10^{-11}	$\text{N m}^2 \text{kg}^{-2}$	$P = Fv$		$v = \pm 2\pi f \sqrt{A^2 - x^2}$	
the Avogadro constant	N_A	6.02×10^{23}	mol^{-1}	$\text{efficiency} = \frac{\text{power output}}{\text{power input}}$		$x = A \cos 2\pi ft$	
molar gas constant	R	8.31	$\text{J K}^{-1} \text{mol}^{-1}$	$\omega = \frac{v}{r} = 2\pi f$		$T = 2\pi \sqrt{\frac{m}{k}}$	
the Boltzmann constant	k	1.38×10^{-23}	J K^{-1}	$a = \frac{v^2}{r} = r\omega^2$		$T = 2\pi \sqrt{\frac{l}{g}}$	
the Stefan constant	σ	5.67×10^{-8}	$\text{W m}^{-2} \text{K}^{-4}$	$I = \sum mr^2$		$\lambda = \frac{\omega s}{D}$	
the Wien constant	α	2.90×10^{-3}	m K	$E_k = \frac{1}{2} I \omega^2$		$d \sin \theta = n\lambda$	
electron rest mass	m_e	9.11×10^{-31}	kg	$\omega_2 = \omega_1 + \alpha t$		$\theta \approx \frac{\lambda}{D}$	
(equivalent to $5.5 \times 10^{-4}u$)				$\theta = \omega_1 t + \frac{1}{2} \alpha t^2$		${}_1n_2 = \frac{\sin \theta_1}{\sin \theta_2} = \frac{c_1}{c_2}$	
electron charge/mass ratio	e/m_e	1.76×10^{11}	C kg^{-1}	$\omega_2^2 = \omega_1^2 + 2\alpha\theta$		${}_1n_2 = \frac{n_2}{n_1}$	
proton rest mass	m_p	1.67×10^{-27}	kg	$\theta = \frac{1}{2} (\omega_1 + \omega_2)t$		$\sin \theta_c = \frac{1}{n}$	
(equivalent to $1.00728u$)				$T = Ia$		$E = hf$	
proton charge/mass ratio	e/m_p	9.58×10^7	C kg^{-1}	$\text{angular momentum} = I\omega$		$hf = \phi + E_k$	
neutron rest mass	m_n	1.67×10^{-27}	kg	$W = T\theta$		$hf = E_1 - E_2$	
(equivalent to $1.00867u$)				$P = T\omega$		$\lambda = \frac{h}{p} = \frac{h}{mv}$	
gravitational field strength	g	9.81	N kg^{-1}	$\text{angular impulse} = \text{change of angular momentum} = Tt$		$c = \frac{1}{\sqrt{\mu_0 \epsilon_0}}$	
acceleration due to gravity	g	9.81	m s^{-2}	$\Delta Q = \Delta U + \Delta W$		Electricity	
atomic mass unit	u	1.661×10^{-27}	kg	$\Delta W = p\Delta V$		$\epsilon = \frac{E}{Q}$	
(1u is equivalent to 931.3 MeV)				$pV^\gamma = \text{constant}$		$\epsilon = I(R + r)$	
Fundamental particles				$\text{work done per cycle} = \text{area of loop}$		$\frac{1}{R_T} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} + \dots$	
Class	Name	Symbol	Rest energy /MeV	$\text{input power} = \text{calorific value} \times \text{fuel flow rate}$		$R_T = R_1 + R_2 + R_3 + \dots$	
photon	photon	γ	0	$\text{indicated power as (area of } p-V \text{ loop)} \times (\text{no. of cycles/s}) \times (\text{no. of cylinders})$		$P = I^2 R$	
lepton	neutrino	ν_e	0	$\text{friction power} = \text{indicated power} - \text{brake power}$		$E = \frac{F}{Q} = \frac{V}{d}$	
		ν_μ	0	$\text{efficiency} = \frac{W}{Q_{\text{in}}} = \frac{Q_{\text{in}} - Q_{\text{out}}}{Q_{\text{in}}}$		$E = \frac{1}{4\pi\epsilon_0} \frac{Q}{r^2}$	
	electron	e^\pm	0.510999	$\text{maximum possible efficiency} = \frac{T_H - T_C}{T_H}$		$E = \frac{1}{2} QV$	
	muon	μ^\pm	105.659			$F = BIl$	
mesons	pion	π^\pm	139.576			$F = BQv$	
		π^0	134.972			$Q = Q_0 e^{-t/RC}$	
	kaon	K^\pm	493.821			$\Phi = BA$	
		K^0	497.762				
baryons	proton	p	938.257				
	neutron	n	939.551				
Properties of quarks							
Type	Charge	Baryon number	Strangeness				
u	$+\frac{2}{3}$	$+\frac{1}{3}$	0				
d	$-\frac{1}{3}$	$+\frac{1}{3}$	0				
s	$-\frac{1}{3}$	$+\frac{1}{3}$	-1				
Geometrical equations							
arc length = $r\theta$							
circumference of circle = $2\pi r$							
area of circle = πr^2							
area of cylinder = $2\pi rh$							
volume of cylinder = $\pi r^2 h$							
area of sphere = $4\pi r^2$							
volume of sphere = $\frac{4}{3}\pi r^3$							

Turn over ►

<p>magnitude of induced emf $= N \frac{\Delta\Phi}{\Delta t}$</p> <p>$I_{\text{rms}} = \frac{I_0}{\sqrt{2}}$</p> <p>$V_{\text{rms}} = \frac{V_0}{\sqrt{2}}$</p> <p>Mechanical and Thermal Properties</p> <p>the Young modulus $= \frac{\text{tensile stress}}{\text{tensile strain}} = \frac{F}{A} \frac{l}{e}$</p> <p>energy stored $= \frac{1}{2} Fe$</p> <p>$\Delta Q = mc \Delta\theta$</p> <p>$\Delta Q = ml$</p> <p>$pV = \frac{1}{3} Nmc^2$</p> <p>$\frac{1}{2} mc^2 = \frac{3}{2} kT = \frac{3RT}{2N_A}$</p> <p>Nuclear Physics and Turning Points in Physics</p> <p>force $= \frac{eV_p}{d}$</p> <p>force $= Bev$</p> <p>radius of curvature $= \frac{mv}{Be}$</p> <p>$\frac{eV}{d} = mg$</p> <p>work done $= eV$</p> <p>$F = 6\pi\eta rv$</p> <p>$I = k \frac{I_0}{x^2}$</p> <p>$\frac{\Delta N}{\Delta t} = -\lambda N$</p> <p>$\lambda = \frac{h}{\sqrt{2meV}}$</p> <p>$N = N_0 e^{-\lambda t}$</p> <p>$T_{\frac{1}{2}} = \frac{\ln 2}{\lambda}$</p> <p>$R = r_0 A^{\frac{1}{3}}$</p>	<p>$E = mc^2 = \frac{m_0 c^2}{\left(1 - \frac{v^2}{c^2}\right)^{\frac{1}{2}}}$</p> <p>$l = l_0 \left(1 - \frac{v^2}{c^2}\right)^{\frac{1}{2}}$</p> <p>$t = \frac{t_0}{\left(1 - \frac{v^2}{c^2}\right)^{\frac{1}{2}}}$</p> <p>Astrophysics and Medical Physics</p> <table> <tr> <th>Body</th><th>Mass/kg</th><th>Mean radius/m</th></tr> <tr> <td>Sun</td><td>2.00×10^{30}</td><td>7.00×10^8</td></tr> <tr> <td>Earth</td><td>6.00×10^{24}</td><td>6.40×10^6</td></tr> </table> <p>1 astronomical unit $= 1.50 \times 10^{11}$ m</p> <p>1 parsec $= 206265 \text{ AU} = 3.08 \times 10^{16}$ m $= 3.26 \text{ ly}$</p> <p>1 light year $= 9.45 \times 10^{15}$ m</p> <p>Hubble constant (H) $= 65 \text{ kms}^{-1} \text{ Mpc}^{-1}$</p> <p>angle subtended by image at eye</p> <p>$M = \frac{\text{angle subtended by image at eye}}{\text{angle subtended by object at unaided eye}}$</p> <p>$M = \frac{f_o}{f_e}$</p> <p>$m - M = 5 \log \frac{d}{10}$</p> <p>$\lambda_{\text{max}} T = \text{constant} = 0.0029 \text{ m K}$</p> <p>$v = Hd$</p> <p>$P = \sigma AT^4$</p> <p>$\frac{\Delta f}{f} = \frac{v}{c}$</p> <p>$\frac{\Delta \lambda}{\lambda} = -\frac{v}{c}$</p> <p>$R_s \approx \frac{2GM}{c^2}$</p>	Body	Mass/kg	Mean radius/m	Sun	2.00×10^{30}	7.00×10^8	Earth	6.00×10^{24}	6.40×10^6	<p>Medical Physics</p> <p>power $= \frac{1}{f}$</p> <p>$\frac{1}{u} + \frac{1}{v} = \frac{1}{f}$ and $m = \frac{v}{u}$</p> <p>intensity level $= 10 \log \frac{I}{I_0}$</p> <p>$I = I_0 e^{-\mu x}$</p> <p>$\mu_m = \frac{\mu}{\rho}$</p> <p>Electronics</p> <p>Resistors</p> <p>Preferred values for resistors (E24)</p> <p>Series: 1.0 1.1 1.2 1.3 1.5 1.6 1.8 2.0 2.2 2.4 2.7 3.0 3.3 3.6 3.9 4.3 4.7 5.1 5.6 6.2 6.8 7.5 8.2 9.1 ohms</p> <p>and multiples that are ten times greater</p> <p>$Z = \frac{V_{\text{rms}}}{I_{\text{rms}}}$</p> <p>$\frac{1}{C_T} = \frac{1}{C_1} + \frac{1}{C_2} + \frac{1}{C_3} + \dots$</p> <p>$C_T = C_1 + C_2 + C_3 + \dots$</p> <p>$X_C = \frac{1}{2\pi fC}$</p> <p>Alternating Currents</p> <p>$f = \frac{1}{T}$</p> <p>Operational amplifier</p> <p>$G = \frac{V_{\text{out}}}{V_{\text{in}}}$ voltage gain</p> <p>$G = -\frac{R_f}{R_1}$ inverting</p> <p>$G = 1 + \frac{R_f}{R_1}$ non-inverting</p> <p>$V_{\text{out}} = -R_f \left(\frac{V_1}{R_1} + \frac{V_2}{R_2} + \frac{V_3}{R_3} \right)$ summing</p>
Body	Mass/kg	Mean radius/m									
Sun	2.00×10^{30}	7.00×10^8									
Earth	6.00×10^{24}	6.40×10^6									